




SERIOUS HEAD PROTECTION

⚠ IMPORTANT.

Read this notice before placing the Chin Guard on your helmet!



1. Clean exterior of helmet to remove all dirt, oil, grease, debris and contaminates using mild soap and water, glass cleaner, or denatured alcohol if available.


Make sure surface is clean, smooth and dry.




2. Prepare two pieces of masking tape and select a pen or marker. Open the shield and apply one piece of tape in the middle of the upper chin bar and another in the middle of the upper chin guard.



3. Without removing the adhesive strips on the back of the chin guard, place the chin guard on the helmet chin bar to self-center the part in the middle.




4. When the chin guard is in a stable position and in the center of the helmet chin bar, use a pen or marker to make a single line or mark over the two masking tapes (it is not necessary for the mark to be in the exact center). This line-mark will guide you in finding the correct position to locate the part during the bonding operation.




5. To bond the part, remove the protective adhesive cover completely on the middle center piece and remove only a small portion of the protective adhesive cover on the side and bottom pieces. Use the detached protective cover on each side as a flap that is wide enough to be used as a handle to apply the chin guard with your fingers.

RS7 CHIN GUARD



6. Place the chin guard on the helmet chin bar at the correct position matching the two marking lines.



7. Press the upper side and middle parts together first, then remove the protective adhesive on the sides and bottom completely and press the part fully in place.



8. Using a soft cloth or microfiber cloth, to press the new chin guard against the helmet chin bar from top to bottom and sides to secure proper bonding between the two parts.



9. Ensure proper functionality of visor and new chin guard. Check to make sure new chin guard is securely attached before use.

For additional information or further instructions, please contact Bell Racing.